## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: EHEIM classicLED daylight

Supplier's address: Service, Plochinger Straße 54, 73779 Deizisau, DE

Model identifier: 4262011 - 740 mm

## Type of light source:

	1		
Lighting technology used:	LED	Non-directional or	NDLS
		directional:	
Light course con tures	24.100		
Light source cap-type	24 V DC,		
(or other electric interface)	ausziehbare		
	Haltebügel,		
	Kunststoffadapter		
	für T5/T8		
Mains or non-mains:	NMLS	Connected light	No
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with
			specific dimmers

Product parameters					
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	12	Energy efficiency class	F		
Useful luminous flux ( $\phi$ use), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 085 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500		
On-mode power (P <sub>on</sub> ), expressed in W	10,6	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-	88		

			values that can be set				
Outer H	leight	6	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page			
	Width	740					
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	vithout Depth eparate ontrol gear, ghting ontrol parts nd non- ghting ontrol parts, any	33					
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-			
			Chromaticity	0,315			
			coordinates (x and y)	0,318			
Parameters for LED and OLED light sources:							
R9 colour renderin	ng index value	39	Survival factor	1,00			
the lumen maintenance factor		0,96					
the lumen mainte	nance factor	0,96					

(a)'-' : not applicable;

(b)'-' : not applicable;

